




LLIFE-D2

CLEVERTRONICS L10 LIFELIGHT, DALI-2



PRODUCT INFORMATION

Part Number	LLIFE-D2
MIC	AUD01210140001
Description	L10 Lithium Nanophosphate Lifelight, recessed Emergency Light, DALI-2
Construction	PC/ABS head
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) , 95mm Head Diameter (145mm with adaptor plate)
Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single white LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 4.5 Watts (Max)
Inrush Current (Max)	12.093mA
Earth Leakage	0.000mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	Battery
AUM01270600001 LLIFE-CKIT-D2	Driver Pack
1100925	LED Head Assembly
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.