



LLIFE-DALI-BLK

CLEVERTRONICS L10 LIFELIGHT, BLACK
(DALI)



PRODUCT INFORMATION

Part Number	LLIFE-DALI-BLK
MIC	UKD01210060002
Description	L10 Lithium Nanophosphate Lifelight, High Performance, Recessed Emergency Light
Construction	PC/ABS Head Double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) , 95mm Head Diameter (145mm with adaptor plate)
Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x LED
Operating Voltage	220-240V AC; 50Hz
Total Lumen Output	188lm (Emergency)
Power Consumption	1.0 Watts (Standby), 4.2 Watts (Max)



LLIFE-DALI-BLK

CLEVERTRONICS L10 LIFELIGHT, BLACK
(DALI)

PRODUCT INFORMATION	
Rated Emergency Duration	180 minutes
IP Rating	IP20
Maximum Case Temperature (TC)	50°C
Operating temperature	0°C to 60°C
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault)

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530031	Battery
1100922	LED Head Assembly
UKM01270040002 LLIFE-CKIT-DALI-450	Driver Pack
8003060	DALI Node