

## Lifelight Emergency, Recessed Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Black



### PRODUCT INFORMATION

Catalogue Number	LLIFE-HVG-BLK
MIC	AUD01910020001
Description	Lifelight Emergency, Recessed Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz, Black
Construction	PC/ABS Head and Control Gear Enclosure
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) 95mm Head Diameter (145mm with adaptor plate)
Ceiling Hole Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Ceiling Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Single white LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 4.5 Watts (MAX)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D40 C <sub>90</sub> =D40

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	BATTERY:L10 3.3V 2.5AH 200mm lead, Brkt
LLIFE-CKIT-HVG	Lifelight: LED, Control Only, L10, HVG (incl. HIVE Node)
1100924	LIFELight Head Assembl, Round, LT, 1LED, Blk
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

*The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order*