



LLIFE-HVG-BLK

Lifelight Emergency, Recessed Mount, L10 Nanophosphate, Zoneworks Hive, Black



PRODUCT INFORMATION

Part Number	LLIFE-HVG-BLK
MIC	UKD01810070002
Description	Lifelight Emergency, Recessed Mount, L10 Nanophosphate, Zoneworks Hive, Black
Construction	PC/ABS Head, Double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Recessed
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) 95mm Head Diameter (145mm with adaptor plate)
Ceiling Hole Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Ceiling Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks HIVE (RF) 2.4GHz
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	1 x LED
Operating Voltage	220-240V AC; 50Hz
Supply Current	0.026A
Power Factor	0.73
Power Consumption	1.3 Watts (Standby), 4.5 Watts (Max)
Inrush Current (Peak/Duration)	0.3A/3668 μ s
Earth Leakage	N/A
Total lumen output	188lm (Emergency)
Rated Emergency Duration	180 minutes
IP Rating	IP20
Operating temperature	0°C to 40°C
Luminaire Classification	X 0 ADF 180
Compliance Marking	
Appliance Class	<input type="checkbox"/> Class II double insulated
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533031	Battery
1100922	LED Panel
UKM01870010002	Emergency Driver
8003330	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.