

## CLEVERTRONICS L10 LIFELIGHT (ZONWORKS XT HIVE)



### PRODUCT INFORMATION

Catalogue Number	LLIFE-HVG
MIC	UKD01810060001
Description	L10 Lithium Nanophosphate Lifelight, High Performance, Recessed Emergency Light
Construction	PC/ABS Head Double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Recessed
Dimensions L x W x H	232mm x 51mm x 42mm (Control Pack) , 95mm Head Diameter (145mm with adaptor plate)
Ceiling Hole Cut-Out	85mm, 135mm (with adaptor plate)
Minimum Ceiling Depth	120mm, 70mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type and Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x LED
Operating Voltage	220-240V AC; 50Hz
Total Lumen Output	188lm (Emergency)
Power Consumption	1.3 Watts (Standby), 4.5 Watts (Max)

### PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Maximum Case Temperature (TC)	50°C				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none"> <li>• Battery overvoltage &amp; overcurrent protection</li> <li>• Battery deep discharge protection</li> <li>• Supply voltage polarity reversal protection</li> <li>• Battery short-circuit protection (charging will resume upon removal of fault)</li> </ul>				
Luminaire Classification	<table border="1"> <tr> <td>X</td> <td>0</td> <td>ADF</td> <td>180</td> </tr> </table>	X	0	ADF	180
X	0	ADF	180		
Conformity	BS EN 60598-2-22, BS 5266				

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530031	BATTERY:L103.3V 2.5AH 260mml,d,NB,Slv,Enc
1100923	UK, LifeLight Head Assembly,Ld:1m, Round, LT, 1LED
UKM01870010001	PCA: LLIFE-CKIT-HVG-450, Lifelight, Control Only, 450mA, L10, OWC
8003250	PCA: UK RF Node CT10720-A1 Ext Antenna

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.