



## LLIFE-HVG

Lifelight Emergency, Recessed Mount,  
L10 Nanophosphate, Zoneworks HIVE



### PRODUCT INFORMATION

Part Number	LLIFE-HVG
MIC	UKD01810060002
Description	Lifelight Emergency, Recessed Mount, L10 Nanophosphate, Zoneworks HIVE
Construction	PC/ABS Head, double/reinforced insulation between supply and battery circuit of lamp control gear
Dimensions L x W x H	Head Diameter 95mm, 145mm with adapter plate Control Pack 232mm x 51mm x 42mm
Ceiling Hole Cut-Out	85mm, 135mm with adapter plate
Minimum Ceiling Depth	120mm, 70mm with adapter plate
Weight	0.84kg
Operating Mode	Non-maintained
Testing System	Zoneworks HIVE (RF)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single white LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 4.5 Watts (Max)
Inrush Current (Peak/Duration)	0.3A / 3668µs
Earth Leakage	N/A
Total lumen output	188lm (Emergency)
Rated Emergency Duration	180 minutes
IP Rating	IP20
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)
Operating Temperature	0°C to 40°C
Compliance Marking	<b>UK</b> <b>CE</b>
Luminaire Classification	X   0   ADF   180
Conformity	BS EN 60598-2-22, BS 5266

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533031	Battery
1100923	LED Head Assembly
UKM01870010002	Driver Pack
8003330	Hive Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order