



LLIFE-PRO-D2-BLK

Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, DALI-2, Black



PRODUCT INFORMATION

Part Number	LLIFE-PRO-D2-BLK
MIC	AUT00000001401
Description	Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, DALI-2, Black
Construction	PC/ABS head
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm head diameter (98mm with adaptor plate)
Ceiling Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz (supplied with a 2 core and earth flex and plug)
Power Consumption	0.7 Watts (Standby), 3.0 Watts (MAX)
Inrush Current (Peak/Duration)	13.313 @ 66µs
Earth Leakage	0.357mA
IP Rating	IP20
IK Rating	IK07
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
AUM01270610001 LLIFE-PRO-CKIT-D2	Driver Pack
1100868	LED Head Assembly
8003062	DALI-2

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.