



## LLIFE-PRO-D2-BLK

Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, DALI-2 Emergency, Black



PRODUCT INFORMATION					
Part Number	LLIFE-PRO-D2-BLK				
MIC	UKT00000005901				
Description	Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, DALI-2 Emergency, Black				
Construction	PC/ABS Head				
Mounting	Recessed Ceiling				
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack), 60mm Head Diameter (98mm with adaptor plate)				
Cut-Out	51mm, 85mm (with adaptor plate)				
Minimum Depth	200mm, 120mm (with adaptor plate)				
Weight	0.8kg				
Operating Mode	Non-maintained				
Testing System	DALI 2				
Battery	Lithium Nanophosphate, 3.3V 5000mAh				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)				
Operating Voltage	240V AC; 50Hz				
Power Consumption	0.7 Watts (Standby), 3.0 Watts (MAX)				
Inrush Current (Max)	13.313A @ 66µs				
Earth Leakage	0.357mA				
IP Rating	IP20				
Operating Temperature	1°C to 40°C				
Luminaire Classification	<table border="1"> <tr> <td>X</td> <td>0</td> <td>ADF</td> <td>180</td> </tr> </table>	X	0	ADF	180
X	0	ADF	180		
Conformity	BS EN 60598-2-22, BS 5266				

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533232	Battery
UKM00000001801	Emergency Driver
1100894	LED Panel
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.