



## LLIFE-PRO-D2-RECWP-BLK

Lifelight Pro IP65 Weatherproof Emergency, Recessed Mount, L10 Nanophosphate, DALI-2 Emergency, Black



### PRODUCT INFORMATION

Part Number	LLIFE-PRO-D2-RECWP-BLK
MIC	UKT00000007701
Description	Lifelight Pro IP65 Weatherproof Emergency, Recessed Mount, L10 Nanophosphate, DALI-2 Emergency, Black
Construction	Die Cast Aluminium Body, 316 Stainless Steel Screws, Clear Toughened Glass
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 120mm diameter (Lamp head)
Ceiling Hole Cut-Out	106mm
Minimum Ceiling Depth	120mm
Operating Mode	Non-maintained
Testing System	DALI-2
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Power Factor	0.366
Supply Current	0.054A
Total lumen output	290lm (Emergency)
Inrush Current (Peak/Duration)	14.0A/77µs
Earth Leakage	0.461mA
Rated Emergency Duration	180 minutes
IP Rating	IP65 (Lamp head only)
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)
Operating Temperature	0°C to 40°C
Luminaire Classification	X 0 AD 180
Conformity	BS EN 60598-2-22, BS 5266
Compliance Marking	UK CA CE

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



## LLIFE-PRO-D2-RECWP-BLK

Lifelight Pro IP65 Weatherproof Emergency, Recessed Mount,  
L10 Nanophosphate, DALI-2 Emergency, Black

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533232	Battery
1100899	LED Panel
UKM01270160002	Emergency Driver
8003062	Node

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.