



LLIFE-PRO-D2-RECWP-WHT

Lifelight Pro IP65 Weatherproof Emergency, Recessed Mount, L10 Nanophosphate, DALI-2



PRODUCT INFORMATION

Part Number	LLIFE-PRO-D2-RECWP-WHT
MIC	AUT01220550001
Description	Lifelight Pro IP65 Weatherproof Emergency, Recessed Mount, L10 Nanophosphate, DALI-2
Construction	Die Cast Aluminium Body, 316 Stainless Steel Screws, Clear Toughened Glass
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 120mm diameter (Head)
Ceiling Hole Cut-Out	106mm
Minimum Ceiling Depth	120mm
Operating Mode	Non-maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max during 16-hour charge)
Inrush Current (Peak/Duration)	12.093A / 87.3µS
Earth Leakage	0.309mA
IP Rating	IP65 (Lamp head only)
IK Rating	IK10 (Lamp head only)
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
1100819	LED Head Assembly
AUM01270610001 LLIFE-PRO-CKIT-D2	Driver Pack
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order