



LLIFE-PRO-D2-SQ

L10 Lithium Nanophosphate LifeLight PRO, high performance, recessed
Emergency Light, DALI-2



PRODUCT INFORMATION

Part Number	LLIFE-PRO-D2-SQ
MIC	AUT00000009101
Description	L10 Lithium Nanophosphate LifeLight PRO, High Performance, Recessed Emergency Light, DALI-2
Construction	PC/ABS head
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 40mm x 40 mm (Control Pack) 60mm x 60mm (Head)
Ceiling Cut-Out	51mm
Minimum Ceiling Depth	200mm
Weight	0.8kg
Operating Mode	Non-Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V~50Hz (supplied with a 2 core and earth flex and plug)
Power Consumption	0.7 Watts (Standby), 3.0 Watts (MAX)
Inrush Current (Max)	13.313/66µs
Earth Leakage	0.357mA
IP Rating	IP20
IK Rating	IK07
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
AUM01270610001 LLIFE-PRO-CKIT-D2	Emergency Driver
1100847	LED Panel
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.