



LLIFE-PRO-D2-SQ-BLK

Lifelight Pro Square Emergency, Recessed Mount, L10 Nanophosphate, DALI-2 Emergency, Black



PRODUCT INFORMATION

Part Number	LLIFE-PRO-D2-SQ-BLK
MIC	AUT00000018501
Description	Lifelight Pro Square Emergency, Recessed Mount, L10 Nanophosphate, DALI-2 Emergency, Black
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm x 60mm (Head)
Cut-Out	51mm
Minimum Depth	200mm
Weight	0.8 kg
Operating Mode	Non-Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Supply Current	0.034A
Power Factor	0.387
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Inrush current (Peak/Duration)	13.313/66µs
Earth Leakage	0.357mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II double insulated

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
1100848	LED Panel
AUM01270610001	Emergency Driver
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.