



## LLIFE-PRO-D2

Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, DALI-2



### PRODUCT INFORMATION

Part Number	LLIFE-PRO-D2
MIC	UKT00000005801
Description	Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, DALI-2
Construction	PC/ABS Head, double/reinforced insulation between supply and battery circuit of lamp control gear
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.6kg
Operating Mode	Non-maintained
Testing System	DALI-2
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V~50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Inrush Current (Max)	14.0A / 77us
Earth Leakage	N/A
Total lumen output	357lm (Emergency)
Rated Emergency Duration	180 minutes
IP Rating	IP20
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)
Operating Temperature	0°C to 40°C
Luminaire Classification	X   0   ADF   180
Compliance Marking	
Conformity	BS EN 60598-2-22, BS 5266

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533232	Battery
1100897	LED Panel
UKM01270160002	Emergency Driver
8003062	Node

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.