

CLEVERTRONICS L10 LIFELIGHT PRO SQUARE, BLACK



PRODUCT INFORMATION

Part Number	LLIFE-PRO-DALI-SQ-BLK
MIC	AUT01210370102
Description	L10 Lithium Nanophosphate LifeLight PRO, high performance, square recessed Emergency Light, Black
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm x 60mm (Head)
Ceiling Hole Cut-Out	51mm
Minimum Ceiling Depth	200mm
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 4.7 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D63 C ₉₀ =D63

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
LLIFE-PRO-CKIT	Lifelight Pro, Control Only, LP/L10
1100835	Lifelight Pro Head Assembly, Round,Black
8003060	PCA: DALI Node #CT10629-Ax

