



# LLIFE-PRO-DALI-SQ

## CLEVERTRONICS L10 LIFELIGHT PRO SQUARE



### PRODUCT INFORMATION

Part Number	LLIFE-PRO-DALI-SQ
MIC	AUT01210360002
Description	L10 Lithium Nanophosphate LifeLight PRO, High Performance, Square Recessed Emergency Light
Construction	PC/ABS Head
Mounting	Recessed Mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm x 60mm (Head)
Cut-Out	51mm
Minimum Depth	200mm
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime Warranty on the Lamp Head and Loom Assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D80 C <sub>90</sub> =D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
AUM01270200002 LLIFE-PRO-CKIT-DALI	Emergency Driver Pack
1100847	LED Head
8003060	Node (DALI)

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.