



LLIFE-PRO-HV-SQ

CLEVERTRONICS L10 LIFELIGHT PRO SQUARE EMERGENCY LUMINAIRE



PRODUCT INFORMATION

Part Number	LLIFE-PRO-HV-SQ
MIC	AUT01810290001
Description	L10 Optimum Lifelight PRO, High Performance, Square Recessed Emergency Light
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm x 60mm (Head)
Cut-Out	51mm
Minimum Depth	200mm
Weight	0.8 kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
1100847	Lifelight Pro Head Assembly, Square, Gen 2, LT
AUM01870010001 LLIFE-PRO-CKIT-HV	Lifelight Pro, Control Only, HV, L10 (incl. Hive node)
8003191	PCA: RF Node CT10678-A12 Int Antenna LLPro

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.