



## LLIFE-PRO-HVG-BLK

CLEVERTRONICS L10 LIFELIGHT PRO, BLACK  
(ZONWORKS XT HIVE)



### PRODUCT INFORMATION

Part Number	LLIFE-PRO-HVG-BLK
MIC	UKT01810150001
Description	L10 Optimum Lifelight PRO, High Performance, Recessed Emergency Light, Black
Construction	PC/ABS Head, double/reinforced insulation between supply and battery circuit of lamp control gear
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.6kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO <sub>4</sub> ), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Total lumen output	357lm (Emergency)

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



## LLIFE-PRO-HVG-BLK

CLEVERTRONICS L10 LIFELIGHT PRO, BLACK  
(ZONWORKS XT HIVE)

### PRODUCT INFORMATION

Rated Emergency Duration	180 minutes			
IP Rating	IP20			
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)			
Operating Temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li><li>• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts</li></ul>			
Luminaire Classification	X	0	ADF	180
Conformity	BS EN 60598-2-22, BS 5266			

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530232	Replacement Battery
1100894	Replacement LED Head Assembly
UKM01870140001 LLIFE-PRO-CKIT-HVG-415	Replacement Driver
8003330	Replacement Communications Node HIVE

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.