

LLIFE-PRO-HVG-RECWP-WHT

Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Zoneworks XT Hive



PRODUCT INFORMATION	
Part Number	LLIFE-PRO-HVG-RECWP-WHT
MIC	UKT01820080002
Description	Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Zoneworks XT Hive
Construction	PC/ABS Head, double/reinforced insulation between supply and battery circuit of lamp control gear
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.6kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF) 2.4GHz
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V ~ 50Hz
Supply Current	0.054A
Power Factor	0.366
Total Lumen Output	357lm (Emergency)
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Inrush Current (Peak/Duration)	14.0A, 77us
Earth Leakage	N/A
IP Rating	IP20
Impact Rating	IK10
Operating Temperature	0°C to 40°C
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)
Rated Emergency Duration	180 minutes
Luminaire Classification	X 0 ADF 180
Compliance Marking	ĽK∣C€
Appliance Class	N/A
Conformity	BS EN 60598-2-22, BS 5266

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.





LLIFE-PRO-HVG-RECWP-WHT Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate,

Zoneworks XT Hive

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1533232	Battery
110-00009	LED Panel
UKM01870050002	Emergency Driver
8003330	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.

