



LLIFE-PRO-HVG-SPOT-BLK

Lifelight Pro Single Spot Emergency, L10 Nanophosphate,
Zoneworks XT Hive, Black



PRODUCT INFORMATION

Part Number	LLIFE-PRO-HVG-SPOT-BLK
MIC	AUT01910070001
Description	Lifelight Pro Single Spot Emergency, L10 Nanophosphate, Zoneworks XT Hive, Black
Construction	PC/ABS Head
Mounting	Lamp head assembly - Ceiling or wall mount with adjustable lamp head direction Control gear and battery - Remote mounted and connected via the standard 1m length of cable (same as the standard Lifelight PRO)
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack), 105mm 100mm x 60mm (Lamp Head and Swivel)
Ceiling Cut-Out	N/A
Weight	0.94kg
Operating Mode	Non-Maintained
Testing System	Zoneworks XT HIVE (RF) 2.4GHz
Battery	Lithium Iron Phosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage charger
Lamp(s)	2 x 3W LED (Lifetime warranty on the lamp head and loom assembly) No dome cover required
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Max), 3.0W (Standby)
Inrush Current (Max)	14.082A@76.7μs
Earth Leakage	0.357mA
IP Rating	IP20
IK Rating	N/A
Operating Temperature	1°C to 40°C
AS2293 Classification	N/A
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
1100817	LED Head Assembly
AUM00000002001 LLIFE-PRO-CKIT-HVG	Driver Pack
8003560	HVG Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.