



LLIFE-PRO-HVG-SQ-BLK

Lifelight Pro Square Emergency, Recessed Mount, L10 Nanophosphate, Zoneworks HIVE, Black



PRODUCT INFORMATION

Part Number	LLIFE-PRO-HVG-SQ-BLK
MIC	AUT01910050001
Description	Lifelight Pro Square Emergency, Recessed Mount, L10 Nanophosphate, Zoneworks HIVE, Black
Construction	PC/ABS head
Mounting	Recessed mount
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm x 60mm (Head)
Cut-Out	51mm
Minimum Depth	200mm
Weight	0.8 kg
Operating Mode	Non-Maintained
Testing System	Zoneworks HIVE (RF) 2.4 GHz
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Supply Current	TBC
Power Factor	TBC
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Inrush current (Peak/Duration)	14.082A / 76.7µs
Earth Leakage	0.357mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
1100848	LED Panel
AUM01970090001	Emergency Driver
8003560	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.