



LLIFE-PRO-HVG-SQ

Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Zoneworks Hive, Square



PRODUCT INFORMATION

Part Number	LLIFE-PRO-HVG-SQ
MIC	UKT01810250002
Description	Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Zoneworks Hive, Square
Construction	PC/ABS Head, double/reinforced insulation between supply and battery circuit of lamp control gear
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm x 60mm (Head)
Ceiling Hole Cut-Out	51mm
Minimum Ceiling Depth	200mm
Weight	0.85kg
Operating Mode	Non-maintained
Testing System	Zoneworks HIVE (RF) 2.4GHz
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO ₄), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Inrush Current (Peak/Duration)	14.0A / 77us
Earth Leakage	N/A
Total lumen output	357lm (Emergency)
Rated Emergency Duration	180 minutes
IP Rating	IP20
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)
Operating Temperature	0°C to 40°C
Compliance Marking	
Luminaire Classification	X 0 ADF 180
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533232	Battery
1100851	LED Head
UKM01870050002	Driver Pack
8003330	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order