



LLIFE-PRO-HVG

L10 Optimum LifeLight PRO, high performance, Recessed Emergency Light, Zoneworks HIVE



PRODUCT INFORMATION

Part Number	LLIFE-PRO-HVG
MIC	AUT01910010002
Description	L10 Optimum LifeLight PRO, high performance, Recessed Emergency Light, Zoneworks HIVE
Construction	PC/ABS Head
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) , 60mm Head Diameter (98mm with adaptor plate)
Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Depth	200mm, 120mm (with adaptor plate)
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF) 2.4GHz
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Factor	0.566
Supply Current	0.05A
Power Consumption	0.5 Watts (Standby), 3.7 Watts (MAX)
Inrush Current (Peak/Duration)	18.5A/142µs
Earth Leakage	0.346mA
IP Rating	IP20
Impact Rating	IK03
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II double insulated

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
AUM01970090002	Emergency Driver
1100868	LED Panel
8003572	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.