





## LLIFE-PRO-RECSP-D2

Lifelight Pro IP44 Splashproof Emergency, Recessed Mount, L10 Nanophosphate, DALI-2 Emergency



PRODUCT INFORMATION	
Part Number	LLIFE-PRO-RECSP-D2
MIC	AUT00000013401
Description	Lifelight Pro IP44 Splashproof Emergency, Recessed Mount, L10 Nanophosphate, DALI-2 Emergency
Construction	PC/ABS head
Mounting	Recessed Ceiling Note: due to the small head/ceiling cut-out, the plug won't fit through the hole and access from behind/above the ceiling is required for installation
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm Head diameter
Ceiling Hole Cut-Out	51mm
Minimum Ceiling Depth	200mm
Operating Mode	Non-maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	220-240V~ 50Hz
Supply Current	0.034A
Power Factor	0.387
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
Inrush current (Peak/Duration)	13.313A / 66µs
Earth Leakage	0.344mA
IP Rating	IP44 (parts below ceiling) IP20 (parts above ceiling), see image below
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II double insulated

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530230	Battery
1100761	LED Panel
AUM01270610001	Emergency Driver
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

IP Ratings:

