



LLIFE-PRO-RECSP-DALI-BLK


Lifelight Pro IP44 Splashproof Emergency, Recessed Mount, L10 Nanophosphate, DALI Emergency, D80, Black



PRODUCT INFORMATION	
Part Number	LLIFE-PRO-RECSP-DALI-BLK
MIC	AUT01220370002
Description	Lifelight Pro IP44 Splashproof Emergency, Recessed Mount, L10 Nanophosphate, DALI Emergency, D80, Black
Construction	PC/ABS head
Mounting	Recessed Ceiling Note: due to the small head/ceiling cut-out, the plug won't fit through the hole and access from behind/above the ceiling is required for installation
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm Head diameter
Ceiling Hole Cut-Out	51mm
Minimum Ceiling Depth	200mm
Operating Mode	Non-Maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP44 (parts below ceiling) IP20 (parts above ceiling), see image below
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530230	Battery
1100763	LED Head Assembly
AUM01270200002 LLIFE-PRO-CKIT-DALI	Driver Pack
8003060	DALI Node

IP Ratings:



The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order