




LLIFE-PRO-RECSP-DALI

CLEVERTRONICS L10 LIFELIGHT PRO RECESSED EMERGENCY LIGHT WITH IP44 SPLASH PROOF HEAD



PRODUCT INFORMATION	
Part Number	LLIFE-PRO-RECSP-DALI
MIC	AUT01220250002
Description	L10 Optimum Lifelight PRO, Recessed Emergency Light with IP44 Splash Proof Head
Construction	PC/ABS head
Mounting	Recessed Ceiling Note: due to the small head/ceiling cut-out, the plug won't fit through the hole and access from behind/above the ceiling is required for installation
Dimensions L x W x H	232mm x 40mm x 40mm (Control pack) 60mm Head diameter
Ceiling Hole Cut-Out	51mm
Minimum Ceiling Depth	200mm
Operating Mode	Non-maintained
Testing System	DALI Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP44 (parts below ceiling) IP20 (parts above ceiling), see image below
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead, Brkt
8050250	LED PCA: HWSUB: CT10666-D1
AUM01270200002 LLIFE-PRO-CKIT-DALI	Lifelight Pro,Control Only, Dali Reg, L10, OWC (incl. Dali node)
8003060	PCA: New DALI #CT10629-Ax

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

IP Ratings:

