



LLIFE-PRO-SM-D2-BLK

Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate,
DALI-2 Emergency, Black



PRODUCT INFORMATION

| | |
|--------------------------------|---|
| Part Number | LLIFE-PRO-SM-D2-BLK |
| MIC | AUT00000006601 |
| Description | Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, Black |
| Construction | Polycarbonate Enclosure |
| Mounting | Surface Mounted |
| Dimensions L x W x H | 242mm x 125mm x 48mm |
| Ceiling Cut-Out | N/A |
| Minimum Ceiling Depth | N/A |
| Weight | 0.7kg |
| Operating Mode | Non-Maintained |
| Testing System | DALI-2 |
| Battery | Lithium Nanophosphate, 3.3V 5000mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Lamp(s) | Dual LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 0.7W (Max), 3.0W (Standby) |
| Inrush Current (Peak/Duration) | 13.313A/66µs |
| Earth Leakage | N/A |
| IP Rating | IP20 |
| IK Rating | N/A |
| Operating Temperature | 1°C to 40°C |
| AS2293 Classification | C0=D80, C90=D80 |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------|
| 1530231 | Battery |
| 8003081 | LED Strip |
| 8003501 | EM Driver |
| 8003062 | DALI-2 Node |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.