



LLIFE-PRO-SM-HVG-BLK

Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate,
Zoneworks HIVE, Black



PRODUCT INFORMATION

Part Number	LLIFE-PRO-SM-HVG-BLK
MIC	AUT01910040001
Description	Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, Zoneworks HIVE, Black
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-maintained
Testing System	Zoneworks HIVE (RF) 2.4GHz
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Supply Current	TBA
Power Factor	TBA
Power Consumption	0.7W (Standby) 3.0 (Max)
Inrush Current (Peak/Duration)	12.1A/88µs
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	<input checked="" type="checkbox"/> Class II double insulated

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	Battery
8003081	LED Panel
8002924	Emergency Driver
8003560	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.