



LLIFE-PRO-SM-HVG

Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate,
Zoneworks XT Hive 2.4GHz



PRODUCT INFORMATION

Part Number	LLIFE-PRO-SM-HVG
MIC	AUT01910020001
Description	Lifelight Pro Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT Hive (RF) 2.4GHZ
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby) 3.0 (Max)
Inrush Current (Peak/Duration)	13.313A/66µs
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D80 C90=D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II double insulated

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	Battery
8003081	LED Head Assembly
8003501	Driver
8003560	HIVE Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.