



LLIFE-PRO-SM-WP-D2

L10 Optimum Lifelight PRO, High Performance, Weatherproof, Surface Mounted Emergency Light, DALI-2



PRODUCT INFORMATION

Part Number	LLIFE-PRO-SM-WP-D2
MIC	AUT01220540001
Description	L10 Optimum Lifelight PRO, High Performance, Weatherproof, Surface Mounted Emergency Light, DALI-2
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	247mm x 129mm x 51mm
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max)
Inrush Current (Peak/Duration)	13.313A/66µs
Earth Leakage	N/A
IP Rating	IP65
IK Rating	IK08
Operating Temperature	0°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II double Insulated

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530231	Battery
8050170	LED Head
8003501	EM Driver
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order