





LLIFE-PRO-SM-WP-D2

Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, DALI-2 Emergency



PRODUCT INFORMATION	
Part Number	LLIFE-PRO-SM-WP-D2
MIC	UKT00000005301
Description	Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, DALI-2 Emergency
Construction	Polycarbonate Enclosure
Mounting	Surface Mount
Dimensions L x W x H	247mm x 129mm x 51mm
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	DALI-2
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Total Lumen Output	350lm (Emergency)
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.7W (Standby) 3.0W (Max)
Inrush Current (Peak/Duration)	14A / 248µs
Rated Emergency Duration	180 minutes
IP Rating	IP65
IK Rating	IK08
Maximum Case Temperature (TC)	-50°C (no heatsink required for lamp control gear)
Operating temperature	0°C to 40°C
Compliance Marking	
Luminaire Classification	X 0 ADF 180
Conformity	BS EN 60598-2-22, BS 5266
Appliance Class	 Class II double insulated

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530231	Battery
8050170	LED Panel
8003840	Emergency Driver
8003062	Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order