



LLIFE-PRO-SM-WP-HVG

Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, L10
Nanophosphate, Zoneworks XT Hive 2.4GHz



PRODUCT INFORMATION

| | |
|--------------------------------|---|
| Part Number | LLIFE-PRO-SM-WP-HVG |
| MIC | AUT01920010001 |
| Description | Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz |
| Construction | Polycarbonate Enclosure |
| Mounting | Surface Mounted |
| Dimensions L x W x H | 247mm x 129mm x 51mm |
| Weight | 0.8kg |
| Operating Mode | Non-maintained |
| Testing System | Zoneworks XT Hive (RF) |
| Battery | Lithium Nanophosphate, 3.3V 5000mAh |
| Charging Method | Intelligent Current Limited Constant Voltage |
| Lamp(s) | Dual LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 240V AC; 50Hz |
| Power Consumption | 0.7W (Standby) 3W (Max) |
| Inrush Current (Peak/Duration) | -13.313/66µs |
| Earth Leakage | N/A |
| IP Rating | IP65 |
| IK Rating | IK08 |
| Operating Temperature | 0°C to 40°C |
| AS2293 Classification | C ₀ =D80 C ₉₀ =D80 |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) |  |
| Appliance Class |  Class II double insulated |

REPLACEMENT PARTS

| PART NUMBER | DESCRIPTION |
|-------------|-------------|
| 1530231 | BATTERY |
| 8050170 | LED |
| 8002924 | DRIVER |
| 8003560 | HVG Node |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.