

LLIFE-PRO-SM-WP-HVG

L10 Lifelight Pro IP65 Weatherproof Surface Mount Emergency, Zoneworks XT Hive (RF) 2.4GHz



PRODUCT INFORMATION	
Part Number	LLIFE-PRO-SM-WP-HVG
MIC	UKT01820040002
Description	L10 Lifelight Pro IP65 Weatherproof Surface Mount Emergency, Zoneworks XT Hive (RF) 2.4GHz
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	247mm x 129mm x 51mm
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF), 2.4GHz
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Total Lumen Output	333lm (Emergency) with Area Lens
Power Consumption	0.7W (Standby) 3.0W (Max)
Rated Emergency Duration	180 minutes
IP Rating	IP65
IK Rating	IK08
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)
Operating temperature	0°C to 40°C
Protection	 Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts
Luminaire Classification	X 0 ADF 180
Conformity	BS EN 60598-2-22, BS 5266

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice





LLIFE-PRO-SM-WP-HVG

L10 Lifelight Pro IP65 Weatherproof Surface Mount Emergency, Zoneworks XT Hive (RF) 2.4GHz

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1533231	Battery
8050170	Emergency LED
8003840	Emergency Driver
8003330	RF Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice

