





LLIFE-PRO-SM-WP

Lifelight Pro IP65 Weatherproof Emergency,
Surface Mount, L10 Nanophosphate, Clevertest Plus



PRODUCT INFORMATION	
Part Number	LLIFE-PRO-SM-WP
MIC	UKT01320080001
Description	Lifelight Pro IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, Clevertest Plus
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	247mm x 129mm x 51mm
Weight	0.7kg
Operating Mode	Non-Maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Nanophosphate, 3.3V 5000mAh, Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.4W (Standby) 2.7W (Max)
Inrush Current (Peak/Duration)	13.313A / 66µs
Earth Leakage	N/A
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Total Lumen Output	333lm (Emergency) with Area Lens
Rated Emergency Duration	180 minutes
IP Rating	IP65
IK Rating	IK08
Operating temperature	0°C to 40°C
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)
Compliance Marking	
Luminaire Classification	X 0 AD 180
Appliance Class	 Class II double insulated
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530231	Battery
8050170	LED Head Assembly
8002958	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order