



LLIFE-PRO-SMC-BLK

CLEVERTRONICS L10 LIFELIGHT PRO CYLINDER
SURFACE MOUNT EMERGENCY - BLACK



PRODUCT INFORMATION	
Part Number	LLIFE-PRO-SMC-BLK
MIC	UKT01310090001
Description	L10 Optimum LifeLight PRO, High Performance, Cylinder Surface Mount Emergency Light, Black, Clevertest Plus Enabled
Construction	Powder coated metal enclosure
Mounting	Surface Mount
Dimensions L x W x H	102mm Diameter x 280mm Height
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.4Watts (Standby), 2.7Watts (Max)
Total lumen output	357lm

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



LLIFE-PRO-SMC-BLK

CLEVERTRONICS L10 LIFELIGHT PRO CYLINDER
SURFACE MOUNT EMERGENCY - BLACK

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts				
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>AD</td><td>180</td></tr></table>	X	0	AD	180
X	0	AD	180		
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
1100809	LED: UK,Lifelight Pro Head Ass,Ld:280mm,Rnd,Gen2,LT,Blk
8002957	PCA: CT10142-L9 2C250/415 CTP DALI DALIREG ZW HVG

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.