




LLIFE-PRO-SMC-D2-BLK

Lifelight Pro Cylinder Emergency, Surface Mount, L10
Nanophosphate, DALI-2 Emergency, Black



PRODUCT INFORMATION

Part Number	LLIFEM-PRO-SMC-D2-BLK
MIC	AUT01210770001
Description	Lifelight Pro Cylinder Emergency, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, Black
Construction	Powder coated metal enclosure, PC/ABS head
Mounting	Surface Mount
Dimensions	128mm Diameter, 245mm Height
Weight	1.9kg
Operating Mode	Non-maintained
Testing System	DALI-2 Registered
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7W (Standby), 3.0W (Max)
Inrush Current (Peak/Duration)	13.313A / 66µs
Earth Leakage	0.362mA
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C ₀ =D80 C ₉₀ =D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	Battery
1100872	LED Head Assembly
AUM01270660001 LLIFE-PRO-SMC-CKIT-D2-NP	Driver Pack
8003062	DALI Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order