



LLIFE-PRO-SMC-D2-BLK

Lifelight Pro Cylinder Emergency, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, Black



PRODUCT INFORMATION

Part Number	LLIFE-PRO-SMC-D2-BLK
MIC	UKT00000011001
Description	Lifelight Pro Cylinder Emergency, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, Black
Construction	Powder coated metal enclosure
Mounting	Surface Mount
Dimensions L x W x H	102mm Diameter x 280mm Height
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	DALI-2
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Total lumen output	357lm
Power Consumption	0.7 Watts (Standby), 3.0 Watts (MAX)
Inrush Current (Peak/Duration)	13.313A @ 66µs
Earth Leakage	0.357mA
IP Rating	IP20
Operating temperature	0°C to 40°C
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)
Rated Emergency Duration	180 minutes
Luminaire Classification	X 0 ADF 180
Compliance Marking	
Conformity	BS EN 60598-2-22, BS 5266

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533230	Battery
1100809	LED Panel
8003839	Emergency Driver
8003062	Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.