



## LLIFE-PRO-SMC-HVG

Lifelight Pro Cylinder Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz



### PRODUCT INFORMATION

Catalogue Number	LLIFE-PRO-SMC-HVG
MIC	AUT01910060001
Description	Lifelight Pro Cylinder Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz
Construction	Powder coated metal enclosure, PC/ABS head
Mounting	Surface Mount
Dimensions	128mm Diameter, 245mm Height
Weight	1.9kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Dual LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	0.7 Watts (Standby), 3.0 Watts (Max)
IP Rating	IP20
Operating Temperature	1°C to 40°C
AS2293 Classification	C <sub>0</sub> =D80 C <sub>90</sub> =D80
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
1100869	Lifelight Pro Head Assembly, Ld:280mm,Rnd,LT,Gen 2
LLIFE-PRO-SMC-CKIT-HVGEXTA-NP	Lifelight Pro, Control Only, SMC, L10, HVGEXTA, NP (incl. HIVE node)
8003580	PCA: V5 2.4GHz RF Node CT10816-A1 Ext Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order.