

LLIFE-PRO-SMC

CLEVERTRONICS L10 LIFELIGHT PRO CYLINDER SURFACE MOUNT EMERGENCY



PRODUCT INFORMATION	
Part Number	LLIFE-PRO-SMC
MIC	UKT01310080001
Description	L10 Optimum LifeLight PRO, High Performance, Cylinder Surface Mount Emergency Light, Clevertest Plus Enabled
Construction	Powder coated metal enclosure
Mounting	Surface Mount
Dimensions L x W x H	102mm Diameter x 280mm Height
Weight	1.5kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.4Watts (Standby), 2.7Watts (Max)
Total lumen output	357lm

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.





LLIFE-PRO-SMC

CLEVERTRONICS L10 LIFELIGHT PRO CYLINDER SURFACE MOUNT EMERGENCY

PRODUCT INFORMATION		
Rated Emergency Duration	180 minutes	
IP Rating	IP20	
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)	
Operating temperature	0°C to 40°C	
Protection	 Battery overvoltage & overcurrent protection Battery deep discharge protection Supply voltage polarity reversal protection Battery short-circuit protection (charging will resume upon removal of fault) Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts 	
Luminaire Classification	X 0 AD 180	
Conformity	BS EN 60598-2-22, BS 5266	

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530230	BATTERY:L10 3.3V 5AH. 200mm lead.Brkt.
1100811	LED:UK,Lifelight Pro,Head Assem,Ld:280mm,Round,Gen2,LT
8002957	PCA: CT10142-L9 2C250/415 CTP DALI DALIREG ZW HVG

^{*}Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.

