



LLIFE-PRO

Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Clevertest Plus



PRODUCT INFORMATION	
Part Number	LLIFE-PRO
MIC	UKT01310030003
Description	Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate, Clevertest Plus
Construction	PC/ABS Head, double/reinforced insulation between supply and battery circuit of lamp control gear
Dimensions L x W x H	232mm x 40mm x 40mm (Control Pack) 60mm Head Diameter (95mm with adaptor plate)
Ceiling Hole Cut-Out	51mm, 85mm (with adaptor plate)
Minimum Ceiling Depth	200mm, 120mm (with adaptor plate)
Weight	0.6kg
Operating Mode	Non-maintained
Testing System	Clevertest Plus Enabled (Not activated by default)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO ₄), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	2 x LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	0.4 Watts (Standby), 2.7 Watts (Max)
Inrush Current (Max)	15.2A
Earth Leakage	0.346mA
Total lumen output	357lm (Emergency)

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



LLIFE-PRO

Lifelight Pro Emergency, Recessed Mount, L10 Nanophosphate,
Clevertest Plus

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)				
Operating temperature	0°C to 40°C				
Protection	• Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) • Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts				
Luminaire Classification	X	0	AD	180	
Conformity	BS EN 60598-2-22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533232	Battery
1100761	LED Head Assembly
UKM01370110002 LLIFE-PRO-CKIT-437	Driver

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.