



## LLIFE-RECSP-HVG

### CLEVERTRONICS L10 LIFELIGHT RECESSED EMERGENCY WITH IP44 SPLASH PROOF HEAD



PRODUCT INFORMATION	
Part Number	LLIFE-RECSP-HVG
MIC	UKD01820020001
Description	L10 Optimum Lifelight, High Performance, Recessed Emergency Light with IP44 Splash Proof Head, Supplied with alternate Corridor Lens
Construction	PC/ABS head
Dimensions L x W x H	232mm x 51mm x 42mm (Control pack) 95mm Head diameter
Ceiling Hole Cut-Out	85mm
Minimum Ceiling Depth	120mm
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Nanophosphate, 3.3V 2500mAh (with battery sleeve), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	1 LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.0 Watts (Standby), 4.2 Watts (Max)
Total lumen output	172lm (Area Lens - fitted), 152lm (Corridor Lens – supplied in box)

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice




# LLIFE-RECSP-HVG

CLEVERTRONICS L10 LIFELIGHT RECESSED EMERGENCY  
WITH IP44 SPLASH PROOF HEAD

PRODUCT INFORMATION				
Rated Emergency Duration	180 minutes			
IP Rating	IP44 (parts below ceiling) IP20 (parts above ceiling), see image below			
Operating temperature	0°C to 40°C			
Protection	<ul style="list-style-type: none"><li>• Battery overvoltage &amp; overcurrent protection</li><li>• Battery deep discharge protection</li><li>• Supply voltage polarity reversal protection</li><li>• Battery short-circuit protection (charging will resume upon removal of fault)</li><li>• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts</li></ul>			
Luminaire Classification	X	0	ADF	180
Conformity	BS EN 60598-2-22, BS 5266			

IP Ratings:



REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530031	BATTERY:L103.3V 2.5AH 260mml,d,NB,Slv,Enc
1100760	Lifelight, WP IP44 Head Assembly
UKM01870010001 LLIFE-CKIT-HVG-450	Lifelight, Control Only, 450mA, L10, HVG, OWC (incl HVG node)
8003250	PCA: UK RF Node CT10720-A1 Ext Antenna

\*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice