



## LLIFE-RECSP-HV

Lifelight IP44 Splashproof Emergency, Recessed Mount, L10 Nanophosphate, Zoneworks XT Hive



### PRODUCT INFORMATION

Part Number	LLIFE-RECSP-HV
MIC	AUD01820020001
Description	Lifelight IP44 Splashproof Emergency, Recessed Mount, L10 Nanophosphate, Zoneworks XT Hive
Construction	PC/ABS head
Mounting	Recessed Ceiling
Dimensions L x W x H	232mm x 51mm x 42mm (Control pack) 95mm Head diameter
Ceiling Hole Cut-Out	80mm
Minimum Ceiling Depth	120mm
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent current limited constant voltage
Lamp(s)	Single LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3 Watts (Standby), 4.5 Watts (Max)
Inrush Current (Max)	0A, 0µs
Earth Leakage	N/A
IP Rating	IP44 (parts below ceiling) IP20 (parts above ceiling), see image below
Operating Temperature	1°C to 40°C
AS2293 Classification	C0=D50 C90=D50
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530010	Battery
1100760	LED Head Assembly
AUM01870020001 LLIFE-CKIT-HV	Driver
8003190	HV Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order

IP Ratings:

