



LLIFE-SM-D2-BLK

Lifelight Emergency, Surface Mount, L10 Nanophosphate,
DALI-2 Emergency, Black



PRODUCT INFORMATION	
Part Number	LLIFE-SM-D2-BLK
MIC	AUT00000015301
Description	Lifelight Emergency, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, Black
Construction	Polycarbonate Enclosure
Mounting	Surface Mount
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-Maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 5000mAh
Charging Method	Intelligent current limited constant voltage charger
Lamp(s)	1 x High Intensity LED (Lifetime warranty on the lamp head and loom assembly)
Operating Voltage	240V 50Hz
Supply Current	0.026A
Power Factor	0.73
Power Consumption	1.3 Watts (Standby), 3.0 Watts (Max)
Inrush current (Peak/Duration)	0.3A/3668µs
Earth Leakage	N/A
IP Rating	IP20
Operating Temperature	1° to 40°C
AS2293 Classification	C0=D40, C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	<input type="checkbox"/> Class II double insulated

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1530071	Battery
8050176	LED Panel
8002939	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order