



LLIFE-SM-D2

Lifelight Emergency, Surface Mount, L10 Nanophosphate,
DALI-2 Emergency



| PRODUCT INFORMATION | |
|--------------------------|---|
| Part Number | LLIFE-SM-D2 |
| MIC | AUD01210190001 |
| Description | Lifelight Emergency, Surface Mount, L10 Nanophosphate, DALI-2 Emergency |
| Construction | Polycarbonate Enclosure1 |
| Mounting | Surface Mount |
| Dimensions L x W x H | 242mm x 125mm x 48mm |
| Weight | 0.7kg |
| Operating Mode | Non-Maintained |
| Testing System | DALI-2 Emergency |
| Battery | Lithium Nanophosphate, 3.3V 5000mAh |
| Charging Method | Intelligent current limited constant voltage charger |
| Lamp(s) | 1 x High Intensity LED (Lifetime warranty on the lamp head and loom assembly) |
| Operating Voltage | 240V 50Hz |
| Power Consumption | 1.3 Watts (Standby), 3.0 Watts (Max) |
| Inrush Current (Max) | 13.313mA @ 66µS 0.248mA |
| Earth Leakage | N/A |
| IP Rating | IP20 |
| Operating Temperature | 1° to 40°C |
| AS2293 Classification | C0=D40, C90=D40 |
| Applicable Standards | AS/NZS3820, CISPR15, AS/NZS2293.3 |
| Compliance Marking (RCM) | |

| REPLACEMENT PARTS | |
|-------------------|------------------|
| PART NUMBER | DESCRIPTION |
| 1530071 | BATTERY |
| 8050176 | LED Assembly |
| 8002939 | Emergency Driver |

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order