



LLIFE-SM-HVG

Lifelight Emergency, Surface Mount, L10 Nanophosphate,
Zoneworks XT Hive



PRODUCT INFORMATION

Part Number	LLIFE-SM-HVG
MIC	UKD01810010002
Description	Lifelight Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive
Construction	Polycarbonate Enclosure
Mounting	Surface Mount
Dimensions L x W x H	242mm x 125mm x 48mm
Weight	0.7kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent current limited constant voltage
Lamp(s)	1 x LED
Operating Voltage	220-240V AC; 50Hz
Power Consumption	1.3Watts (Standby), 3.0Watts (Max)
Total lumen output	195lm (Emergency)

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.



LLIFE-SM-HVG

Lifelight Emergency, Surface Mount, L10 Nanophosphate,
Zoneworks XT Hive

PRODUCT INFORMATION

Rated Emergency Duration	180 minutes				
IP Rating	IP20				
Operating temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp control gear provides protection against accidental contacts with live parts				
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>ADF</td><td>180</td></tr></table>	X	0	ADF	180
X	0	ADF	180		
Applicable Standards	BS EN 60598-2-22, BS 5266				
Compliance Marking					

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533071	Battery
8050176	LED Head Assembly
8003822	Driver
8003330	HIVE Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.