



LLIFE-SM-WP-BLK

Lifelight IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, Clevertest Plus, Black



PRODUCT INFORMATION

Part Number	LLIFE-SM-WP-BLK				
MIC	UKT00000008001				
Description	Lifelight IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, Clevertest Plus, Black				
Construction	Polycarbonate Enclosure				
Mounting	Surface Mounted				
Dimensions L x W x H	247mm x 129mm x 51mm				
Weight	0.8kg				
Operating Mode	Non-maintained				
Testing System	Clevertest Plus Enabled (Not activated by default)				
Battery Type & Manufacturer	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	1 x LED				
Operating Voltage	220-240V AC; 50Hz				
Supply Current	TBC				
Power Factor	TBC				
Total Lumen Output	180lm (Area Lens)				
Power Consumption	1.0 (Standby) 4.2W (Max)				
Inrush Current (Peak/Duration)	TBC				
Earth Leakage	TBC				
Rated Emergency Duration	180 minutes				
IP Rating	IP65				
IK Rating	IK08				
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)				
Operating temperature	0°C to 40°C				
Compliance Marking					
Luminaire Classification	<table border="1"><tr><td>X</td><td>0</td><td>AD</td><td>180</td></tr></table>	X	0	AD	180
X	0	AD	180		
Conformity	BS EN 60598.2.22, BS 5266				
Appliance Class	<input type="checkbox"/> Class II double insulated				



LLIFE-SM-WP-BLK

Lifelight IP65 Weatherproof Emergency, Surface Mount, L10
Nanophosphate, Clevertest Plus, Black

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1533071	Battery
8050174	LED Panel
8003822	Emergency Driver

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order