





## LLIFE-SM-WP-D2

Lifelight IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, DALI-2 Emergency



### PRODUCT INFORMATION

Part Number	LLIFE-SM-WP-D2
MIC	AUD01220080001
Description	Lifelight IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, DALI-2 Emergency
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	247mm x 129mm x 51mm
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x High intensity LED
Operating Voltage	240V AC; 50Hz
Power Factor	TBA
Supply Current	TBA
Power Consumption	1.3W (Standby) 4.5W (Max)
Inrush Current (Peak/ Duration)	0.3A/3668µs
Earth Leakage	N/A
IP Rating	IP65
IK Rating	IK08
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	
Appliance Class	 Class II Double Insulated

### REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530071	Battery
8002939	Emergency Driver
8050174	LED Panel
8003062	Node