




LLIFE-SM-WP-D2

Lifelight IP65 Weatherproof Emergency, Surface Mount,
L10 Nanophosphate, DALI-2 Emergency,
including optional Corridor lens



PRODUCT INFORMATION	
Part Number	LLIFE-SM-WP-D2
MIC	UKT00000005201
Description	Lifelight IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, DALI-2 Emergency, including optional Corridor lens
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions	247mm x 129mm x 51mm
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	DALI-2
Battery	Lithium Nanophosphate (LiFePO4), Clevertronics
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x LED
Operating Voltage	220-240V AC; 50Hz
Total Lumen Output	180lm (Area Lens)
Power Consumption	1.3W (Standby) 4.5W (Max)
Inrush Current (Peak/Duration)	0.3A / 3668µs
Earth Leakage	N/A
IP Rating	IP65
IK Rating	IK08
Rated Emergency Duration	180 Minutes
Operating Temperature	0°C to 40°C
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp control gear)
Compliance Marking	
Luminaire Classification	X 0 ADF 180
Conformity	BS EN 60598.2.22, BS 5266

REPLACEMENT PARTS	
PART NUMBER	DESCRIPTION
1533071	Battery
8003060	Emergency Driver
8050174	Emergency LED
8003062	DALI-2 Node

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order