



LLIFE-SM-WP-HVG-BLK

Lifelight IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, including optional Corridor Lens, Black



PRODUCT INFORMATION

Part Number	LLIFE-SM-WP-HVG-BLK				
MIC	UKT00000004401				
Description	Lifelight IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive, including optional Corridor Lens, Black				
Construction	Polycarbonate Enclosure				
Mounting	Surface Mounted				
Dimensions L x W x H	247mm x 129mm x 51mm				
Weight	0.8kg				
Operating Mode	Non-maintained				
Testing System	Zoneworks XT Hive (RF)				
Battery	Lithium Nanophosphate (LiFePO4), Clevertronics				
Charging Method	Intelligent Current Limited Constant Voltage				
Lamp(s)	1 x LED				
Operating Voltage	220-240V AC; 50Hz				
Total Lumen Output	180lm (area Lens)				
Power Consumption	1.3W (Standby) 4.5W (Max)				
Rated Emergency Duration	180 Minutes				
IP Rating	IP65				
IK Rating	IK08				
Maximum Case Temperature (TC)	50°C (No heatsink required for lamp controlgear)				
Operating Temperature	0°C to 40°C				
Protection	<ul style="list-style-type: none">• Battery overvoltage & overcurrent protection• Battery deep discharge protection• Supply voltage polarity reversal protection• Battery short-circuit protection (charging will resume upon removal of fault)• Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts				
Luminaire Classification	X	0	ADF	180	
Conformity	BS EN 60598.2.22, BS 5266				

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530071	Battery
8050174	LED
8002907	EM Driver
8003250	ZW Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice