



LLIFE-SM-WP-HVG

Lifelight IP65 Weatherproof Emergency, Surface Mount, L10
Nanophosphate, Zoneworks XT Hive 2.4GHz



PRODUCT INFORMATION

Part Number	LLIFE-SM-WP-HVG
MIC	AUD01920010001
Description	Lifelight IP65 Weatherproof Emergency, Surface Mount, L10 Nanophosphate, Zoneworks XT Hive 2.4GHz
Construction	Polycarbonate Enclosure
Mounting	Surface Mounted
Dimensions L x W x H	247mm x 129mm x 51mm
Weight	0.8kg
Operating Mode	Non-maintained
Testing System	Zoneworks XT HIVE (RF)
Battery	Lithium Nanophosphate, 3.3V 2500mAh
Charging Method	Intelligent Current Limited Constant Voltage
Lamp(s)	1 x High intensity LED
Operating Voltage	240V AC; 50Hz
Power Consumption	1.3W (Standby) 4.5W (Max)
IP Rating	IP65
IK Rating	IK08
Operating Temperature	0°C to 40°C
AS2293 Classification	C0=D40 C90=D40
Applicable Standards	AS/NZS3820, CISPR15, AS/NZS2293.3
Compliance Marking (RCM)	

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530071	BATTERY:L10 3.3V 2.5AH 200mm ld, no Brkt
8002939	Driver: PCA: LLIFE CT10260-L5 1C550 HV DaliReg Vert Con
8050174	LED: PCA: HWSUB: CT10694-D1
8003560	PCA: V5 2.4GHz RF Node CT10816-A1 Int Ant

The product details described in this document are current as at the version date of the document. We reserve the right to change product design, specifications or materials (Specifications) as part of our continuous improvement program. Please confirm the applicable Specifications at the time of placing your order