



LLIFE-SM-WP-HVG

L10 Lifelight IP65, Weatherproof, Surface Mount, Emergency, Zoneworks XT Hive (RF) 2.4GHz



PRODUCT INFORMATION

Part Number	LLIFE-SM-WP-HVG			
MIC	UKD01820010002			
Description	L10 Lifelight IP65, Weatherproof, Surface Mount, Emergency, Zoneworks XT Hive (RF) 2.4GHz			
Construction	Polycarbonate Enclosure			
Mounting	Surface Mounted			
Dimensions L x W x H	247mm x 129mm x 51mm			
Weight	0.8kg			
Operating Mode	Non-maintained			
Testing System	Zoneworks XT HIVE (RF), 2.4GHz			
Battery	Lithium Nanophosphate (LiFePO4), Clevertronics			
Charging Method	Intelligent Current Limited Constant Voltage			
Lamp(s)	1 x LED			
Operating Voltage	220-240V AC; 50Hz			
Total Lumen Output	180lm (Area Lens)			
Power Consumption	1.3W (Standby) 4.5W (Max)			
IP Rating	IP65			
IK Rating	IK08			
Maximum Case Temperature (TC)	50°C (no heatsink required for lamp controlgear)			
Operating temperature	0°C to 40°C			
Protection	• Battery overvoltage & overcurrent protection • Battery deep discharge protection • Supply voltage polarity reversal protection • Battery short-circuit protection (charging will resume upon removal of fault) • Kit box (enclosure) of lamp controlgear provides protection against accidental contacts with live parts			
Luminaire Classification	X	0	ADF	180
Conformity	BS EN 60598.2.22, BS 5266			

REPLACEMENT PARTS

PART NUMBER	DESCRIPTION
1530071	Battery
8050174	Emergency Driver
8002907	Emergency LED
8003250	UK RF Node

*Due to changes in industry standards and Clevertronics policy of product improvement, specification details are subject to change without notice.